

Product Description

Hepburn is an elegant combination of classic looks and advanced modern technology. This is a family of miniaturized LED spotlight designed to achieve smallest size of the same power in industry, therefore to meet visual and aesthetic requirement for interior design. Small body can reduce thermal contact resistance and help for heat dissipation. Meanwhile, adoption of advanced thermal superconductor technology with 300,000w/mk guarantees heat generated from LED being instantly transferred and radiated into the air. This keeps the fitting in good lumen maintenance and long lifespan. Hepburn is designed in a variety of different installations to be the perfect match for every environment.

Product Specification

Luminaire Wattage	30W
Luminaire Color	<input type="checkbox"/> White <input checked="" type="checkbox"/> Black
Light Source	LUMINUS CLM-9AC40 1x30W DC700r
Color Temperature	2700K/3000K/4000K/5000K
Color Rendering Index	Ra≥90
Beam Angle	15°/24°/38°
Luminous Flux	2200lm at 3000K
Driver	LS-40-700 LI2
Power Factor (PF)	≥0.90
Input	AC220-240V 50-60Hz
Output	DC700mA 30V-42V
Class	Class II
IP Degree	IP20
Cut out	Ø80MM
Inner Box	12.5*12.5*11.8cm
Carton Size	52*26*37cm
QTY/CTN	24PCS/CTN
Net Weight	0.34KG/PCS


Model No.

HB.D130S

CONTACT US FOR MORE DETAILS

[Weblink](#)

CCC CE RoHS



Light Distribution

3000K 15°

3000K 24°

3000K 38°

	h(m)	E(lx)	D(m)		h(m)	E(lx)	D(m)		h(m)	E(lx)	D(m)
			15°				24°				38°
	1	20331	0.21		1	10600	0.36		1	5605	0.54
	2	5082	0.42		2	2650	0.72		2	1401	1.08
	3	2259	0.62		3	1177	1.08		3	622	1.61
	4	1270	0.83		4	663	1.44		4	350	2.15

Related references

Optional Accessories



Honeycomb

Size: 52×3



Combed Glass

Size: 52×3



Woven Glass

Size: 52×3

Related references

LED POWER SUPPLIES



Constant current power supply

Triac

0-10V

Dali

Related project picture of product family:

