

Product Description

Modular Lighting System 48V combines unornamented aesthetics with a multitude of configuration options and effortless installation. The outcome is an ecosystem of quality components perfect for spaces where constant flexibility and high performance are required.

Product Specification


Luminaire Wattage	6W
Luminaire Color	<input type="checkbox"/> White <input checked="" type="checkbox"/> Black
Light Source	Honourtek
Color Temperature	2700K/3000K/3500K/4000K/500
Color Rendering Index	Ra≥95
Beam Angle	15°/24°/36°
Luminous Flux	420lm at 3000K
Driver	P61-4807-BM01-I
Input	48V
Output	DC150mA 1X6W
Class	Class III
IP Degree	IP20
Adaptor	48v dapter
Inner Box	19.5x12x6cm
Carton Size	41x38x32CM
QTY/CTN	30PCS/CTN
Net Weight	0.25KG/PCS

Model No.

DC.PS0206-C

CONTACT US FOR MORE DETAILS

WebLink




Light Distribution


15°

24°


36°



h(m)	E(lx)	D(m)
1	1857	0.34
2	464	0.68
3	206	1.02
4	116	1.36



h(m)	E(lx)	D(m)
1	1321	0.42
2	330	0.84
3	146	1.26
4	82	1.68



h(m)	E(lx)	D(m)
1	815	0.59
2	203	1.17
3	90	1.76
4	50	2.35

Ledoux

Related project picture of product family:

