Ledoux

Product Description

Product Specfication Luminaire Wattage

Luminaire Color

Color Temperature Color Rending Index

Light Source

Beam Angle

Luminous Flux

Power Factor (PF)

cut-out Driver

Input

Output

Class

IP Degree

Inner Box

Carton Size

OTY/CTN

Net Weight

simple slim housing and integration of housing as heatsink. This not only makes its :imple modern appearance, also guarantee LED lifespan and lighting output. Also, hidden I ght source makes healthy and comfortable lights. for small space, and high end club, museum, notel, gallery and etc. Together with inner ring of optional colors, the fitting becomes fresl and attractive. Eos recessed spot light is featured by Simple slim housing makes it applicable

10W

Ra≥90

15°/24°/38°

872lm/3000K Ø80MM

LD9W250

Ac100-240V

CLASS I

10X10X21.5cm

42X42X23.5cm

16PCS/CTN 0.43KG/PCS

844

474

IP20

DC660-700mA 3-12V

≥0.50

White Black

LUMINUS CXM-6 AC40 1X10W [2700K/3000K/3500K/4000K

~000	JUCU	Data	Sheet





Light Distribution

3000K 15°				
HAK	h(m)	E(lx)		
XHHX	Ĩ	7596		
AL	0	1000		

15°	h(m
0.30	10
0.60	2
0.90 AA	3

D(m) n) E(lx) 24°

0.40

0.81

1.61

4887

543

305

3000K 24°

3000K **36°**

TAK.	h(m)	E(lx)	D(m) 36°
\times	1	2291	0.60
VH+HC	2	572	1.21
MK	3	254	1.81
2292	4	143	2.41

Ledoux

Related references Optional Accessories for Baffle













Golden



Optional Accessories

Optional Colors

Honeycomb Size: 33×3

Combed Glass Size: 33×3

Woven Glass Size: 33×3

White

Black





Constant current power supply

Dali

Ledoux

Related project picture of product family:

