

Product Description

- 1.Lamp light source uses OSRAM Chip, with pure light color and CRI>90.
- 2.Front ring adopts 316L stainless steel material with Anti-rust passivation process for outdoor use.
- 3.The lamp body is processed by CNC aluminum , and the surface is sprayed with Aksu outdoor paint (double-layer coating process).
- 4.Multiple beam angles are available with uniform illumination.
- 5.The light source is hidden deeply, with 40°anti-glare cut-off angle.
- 6.With anti-glare honeycomb.
- 7.The lamp with exquisite structure,suitable for buildings,gardens and other places.

Product Specification


Luminaire Wattage	1.7W
Luminaire Color	■ Black
Light Source	OSRAM OSOLON 150
Color Temperature	2700K/3000K/3500K/4000K
Color Rending Index	Ra≥90
Beam Angle	20°/30°
Luminous Flux	60lm at 3000K
cut-out	/
Driver	DC24V驱动
Power Factor (PF)	≥0.5
Input	AC220-240V 50-60Hz
Output	Ø23
Class	ClassIII
IP Degree	IP67
Adaptor	/
Inner Box	7X6X4.8cm
Carton Size	16X32X28cm
QTY/CTN	50PCS/CTN
Net Weight	0.09KG/PCS

Model No.

BSB0502-C


CONTACT US FOR MORE DETAILS

WebLink




Light Distribution

3000K 20°



h(m)	E(lx)	D(m)
		20°
1	369	0.37
2	92	0.75
3	41	1.12
4	23	1.49

3000K 30°



h(m)	E(lx)	D(m)
		30°
1	98	0.57
2	24	1.15
3	11	1.72
4	6	2.30

Related references

Optional Accessories



Honeycomb

Size:Ø10x3mm

Combed Glass

Size:/

Woven Glass

Size:/