

Product Description

Modular Lighting System 48V combines unornamented aesthetics with a multitude of configuration options and effortless installation. The outcome is an ecosystem of quality components perfect for spaces where constant flexibility and high performance are required.

Product Specification


Luminaire Wattage	3W
Luminaire Color	<input type="checkbox"/> White <input checked="" type="checkbox"/> Black
Light Source	LUMINUS
Color Temperature	2700K/3000K
Color Rendering Index	Ra>95
Beam Angle	15°/24°/30°
Luminous Flux	130lm at 3000K
Driver	P63-4806C-BM17
Input	48V
Output	DC700mA 1X3W
Class	Class III
IP Degree	IP20
Inner Box	10.5X8X3cm
Carton Size	23X26X35cm
QTY/CTN	66PCS/CTN
Net Weight	0.07KG/PCS

Model No.

DC.TS0103-1


CONTACT US FOR MORE DETAILS

[WebLink](#)




Light Distribution

15°




h(m)	E(lx)	D(m)
1	374	0.40
2	93	0.80
3	41	1.20
4	23	1.60

24°



h(m)	E(lx)	D(m)
1	207	0.53
2	51	1.06
3	23	1.59
4	12	2.12

30°



h(m)	E(lx)	D(m)
1	120	0.74
2	29	1.48
3	13	2.22
4	7	2.96

Ledoux

Related project picture of product family:

