

Product Description

Hepburn is an elegant combination of classic looks and advanced modern technology. This is a family of miniaturized LED spotlight designed to achieve smallest size of the same power in industry, therefore to meet visual and aesthetic requirement for interior design. Small body can reduce thermal contact resistance and help for heat dissipation. Meanwhile, adoption of advanced thermal superconductor technology with 300,000w/mk guarantees heat generated from LED being instantly transferred and radiated into the air. This keeps the fitting in good lumen maintenance and long lifespan. Hepburn is designed in a variety of different installations to be the perfect match for every environment.

Product Specification

Luminaire Wattage	90W
Luminaire Color	□ White ■ Black
Light Source	Luminus CHM-22
Color Temperature	3000K/4000K/5000K
Color Rendering Index	Ra≥80
Beam Angle	18°/28°/38°
Luminous Flux	8179lm/3000K
cut-out	Ø165mm
Driver	LPC-100-2100
Power Factor (PF)	≥0.50
Input	AC90-240V
Output	DC2100mA 24-48V
Class	CLASS III
IP Degree	IP20
Inner Box	22.5X19X21.5cm
Carton Size	47X40X45cm
QTY/CTN	8PCS/CTN
Net Weight	1.1KG/PCS

Model No.

DSA0890-C

CONTACT US FOR MORE DETAILS




CE RoHS




Light Distribution

3000K 15°




h(m)	E(lx)	D(m)
1	35215	0.32
2	8803	0.64
3	3912	0.96
4	2200	1.28

3000K 28°



h(m)	E(lx)	D(m)
1	19978	0.51
2	4994	1.02
3	2219	1.53
4	1248	2.04

3000K 38°



h(m)	E(lx)	D(m)
1	14343	0.73
2	3585	1.45
3	1593	2.18
4	896	2.91

Related references

LED POWER SUPPLIES



Constant current power supply

Triac

0-10V

Dali

Related project picture of product family:

