Ledoux


Product Description

Yoda recessed spot light series are popular for its modular design and its different installation ways: fixed or adjustable, trim or trimless, for direct lighting or wall washing. With the feature of dark light reflector,Yoda provides a high level of comfortable visual and optimum light output ratio. Different optical design are available for various occassions, including diffuser for general lighting, optical lens with narrow beam angle 4°/6°/8° & common beam angle 15°/24°/36°/50°, special asymmetric wall washer lens for wall washer, and zoomable option. Mounted accessories can be ordered separately for different application requirements or easy replacement.

Product Specfication

| Luminaire Wattage | 10W |
|----------------------|---------------------------------|
| Luminaire Color | U White Black |
| Light Source | HonourTEK HRB0607 |
| Color Temperature | 2700K/3000K/4000K/5000K |
| Color Rending Index | Ra≥95 |
| Beam Angle | 15°/24°/36°/55° |
| Luminous Flux | 846lm at 3000K |
| cut-out | ø75 |
| Driver | LS-12-250 SI3 |
| Power Factor (PF) | ≥0.50 |
| Input | AC220-240V 50-60Hz |
| Output | DC250mA 36V |
| Class | Class II |
| IP Degree | IP20 |
| Inner Box | 13X13X8cm |
| Carton Size | 41X28X26cm |
| QTY/CTN | 18PCS/CTN |
| Net Weight | 0.19KG/PCS |
| LED POWER SUPPLIES | Triac\0-10V\Dali |
| Optional Accessories | Honeycomb\Woven Glass\Combed Gl |





Light Distribution

| 3000K 15° | 3 | 3000K 24° | | 3000K 369 | o | 300 | 0K 55° | |
|--|---|---|---|--------------------------|---|-------------|--|---|
| h(m) E(lx) 1 5426 2 1356 3 602 4 339 | D(m) 15° 0.33 0.67 1.00 1.34 | h(m) E(lx) 1 3683 2 920 3 409 4 230 | D(m) 24° 0.45 0.89 1.34 1.78 | h(m) 1 2 3 4 | E(lx) D(r 36° 2374 0.6 593 1.2 263 1.8 148 2.4 | 2 3 5 | h(m) E(lx) 1 1055 2 263 3 117 4 65 | D(m) 55° 1.04 2.09 3.13 4.18 |