

Product Description


- 1.Lamp light source uses OSRAM Chip, with pure light color and CRI>90。
- 2.The lamp body is processed by CNC aluminum+Aluminum heat sink , and the surface is sprayed with Aksu outdoor paint (double-layer coating process:.)。
- 3.Multiple beam angles are available with uniform illumination.
- 4.The light source is hidden deeply, with 40°anti-glare cut-off angle。
- 5.With anti-glare honeycomb.
- 6.The lamp with mini and exquisite structure,suitable for buildings,gardens and other places.
- 7.Ground plug/Baffle are optional accessories, needs be ordered seperately.

Product Specification

Luminaire Wattage	2.6W
Luminaire Color	■ Black
Light Source	OSRAM OSLON 150
Color Temperature	2700K/3000K/3500K/4000K
Color Rendering Index	Ra≥90
Beam Angle	20°/30°
Luminous Flux	92lm at 3000K
cut-out	/
Driver	DC24V驱动
Power Factor (PF)	≥0.5
Input	AC220-240V 50-60Hz
Output	/
Class	Class II
IP Degree	IP66
Adaptor	/
Inner Box	7X6X4.8cm
Carton Size	16X32X28cm
QTY/CTN	50PCS/CTN
Net Weight	0.1KG/PCS


Light Distribution

3000K 20°



h(m)	E(lx)	D(m)
		20°
1	530	0.39
2	132	0.77
3	59	1.16
4	33	1.55

3000K 30°




h(m)	E(lx)	D(m)
		30°
1	173	0.58
2	43	1.16
3	19	1.74
4	10	2.31

Model No.

GSA0502-C

CONTACT US FOR MORE DETAILS

WebLink



Related references

Optional Accessories



Honeycomb
Size: Ø12x2mm

Combed Glass
Size: /

Woven Glass
Size: /