

Product Description

Product Specfication

Luminaire Wattage

Color Rending Index

Power Factor (PF)

Luminaire Color

Light Source Color Temperature

Beam Angle Luminous Flux

Driver

Input

Output Class

IP Degree

Adaptor Inner Box

Carton Size

Net Weight

Eos track spot light is featured by housing as heatsink. This not only makes its simple modern appearance also guarantee LED lifespan and lighting output. Also hidden light source makes healthy and comfortable lights. for small space and high end club museum hotel gal ery and etc. Together with inner ring of optional colors the fitting becomes fresh and attract ve. Simple slim housing makes it applicable museum,hotel,gallery and etc. Together with inner ring of optional colors the fitting becomes fresh and attractive.

15W

U White Black

2700K-6000K

900lm at 3000K CY15WFU-40X350

AC220-240V 50-60Hz DC350mA 35V

One Phase/Three Phase

25.5*10*7.5cm

24PCS/CTN

0.82KG/PCS

Ra≥90 15°/24°/36°

≥0.90

Class I

IP20

ern es nd mple f	CONTACT US FOR MORE DETAILS	<u>Weblink</u>

Light Distribution

3000K 15°			3000K 24°			3000K 36°			
h(r	n) E(lx) 4166	D(m) 15° 0.34	h(m)	E(lx)	D(m) 24° 0.47		h(m)	E(lx) 2214	D(m) 36° 0.59
	1041 462 260	0.67 1.01 1.34	2 3 4	665 295 166	0.93 1.40 1.86	225	2 3 4	553 246 138	1.81 1.76 2.35

Ledoux

Related references Optional Accessories





Honeycomb Size: Ø 52×3

Related references Optional Color for baffle







Optional Accessories

www.ledouxlight.com

White	Golden	Black	
Constant current power supp		iac	0-10V
constant carrent power supp			0.104

Ledoux

Related project

Dali

Related project picture of product family:

