

## Product Description

The Union is combining elegance and flexibility. It's available in track or ceiling surface mounted version. Featuring with deep baffle and achieving a high level of visual comfort. The upper and lower body can be moved and angled in a very dynamic and fluid way. Also the fitting is rotating by 360° flexible for multiple installation requirements. Innovative thermal design to incorporate pure aluminum body as heatsink and air convection cooling guarantees LED's stable performance and long lifespan.

**Model No.** TSU3015-C


CONTACT US FOR MORE DETAILS

[WebLink](#)




## Product Specification

Luminaire Wattage	15W
Luminaire Color	<input type="checkbox"/> White <input checked="" type="checkbox"/> Black
Light Source	CR13071202PD30E38
Color Temperature	2700K/3000K/4000K
Color Rendering Index	Ra≥90
Beam Angle	D55调焦
Luminous Flux	949lm at 3000K
Driver	LN-L086 15W
Power Factor (PF)	≥0.50
Input	AC200-240V 50-60Hz
Output	DC350mA 30-42V
Class	Class I
IP Degree	IP20
Inner Box	20*20*8cm
Carton Size	42*21.5*26cm
QTY/CTN	6PCS/CTN
Net Weight	0.60KG/PCS




## Light Distribution

3000K 12°



h(m)	E(lx)	D(m)
		12°
1	9028	0.26
2	2257	0.52
3	1003	0.78
4	564	1.04

3000K 55°



h(m)	E(lx)	D(m)
		55°
1	1892	0.81
2	473	1.62
3	210	2.43
4	118	3.24

Related references  
**LED POWER SUPPLIES**



Constant current power supply



Triac

0-10V

Dali